



Product Category: 05 41 00 - Structural Framing

**Product Name:** 1000S250-68

#### **Important Properties Notes:**

- Calculated properties are based on AISI S100-12 with S2-10
   Supplement, North American Specification for Design of Cold-Formed
   Steel Structural Members.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on fullsection of the studs, away from punchouts.
- · For deflection calculations, use the effective
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be

specified. (ex. 362S162-43 (50 ksi))

#### **Project Information**

Name: Address:

# **Contractor Information** Name:

Name: Contact: Phone: Fax:

#### **Architect Information**

Name: Contact: Phone: Fax:


#### **Distributor/Rep Information**

Name: Contact: Phone: Email /Web:

## **Properties**

## **1000S250-68 Properties**

Finish:	G60
Web Depth	10" in
Flange Width	2 1/2 in
Design Thickness	0.0713 in
Thickness	68 mils or 14GA
Yield stress, Fy	50 ksi
Weight	3.814 lb/ft



## 1000S250-68 Section Properties

## **Gross Section Properties**

Cross sectional area (A)	1.121 I <b>n</b> 2
Moment of inertia (Ix)	15.756 In4
Section Modulus (Sx)	3.151 in3
Radius of gyration (Rx)	3.749 in
Gross moment of inertia (ly)	0.799 in4
Gross Radius of gyration (Ry)	0.844 in

## **Effective Section Properties**

Moment of inertia for deflection (lxe)	15.198	in4
Section modulus (Sxe)	2.765	in3
Allowable bending moment (Ma)	82.79	In-k
Allowable bending moment from	69.4	In-K
distortional buckling (Mad)		
Allowable strong axis shear away	3345	lb
from punch-out (Vag)		
Allowable strong axis shear at	3345	lb
punch out (Vanet)		

### **Torsional Properties**

St. Venant torsion constant (J x 1000)	1.899 in4
Warping constant (Cw)	15.909 in6
Distance from shear center to neutral	-1.488 in
axis (Xo)	
Distance from shear center to	0.95 in
mid-plane (M)	
Radii of gyration (Ro)	4.121 in
Torsional flexural constant (Beta)	0.87
Unbraced Length (Lu)	48.8 in

1000S250-68 Page 1



Product Category: 05 41 00 - Structural Framing

**Product Name:** 1000S250-68

## **Limiting Heights Properties**

## Limiting Wall Heights - Curtain Wall 1-Span

Spacing	5psf			15psf			20psf			25psf		
(inches)	L/120	L/240	L/360	L/240	L/360	L/600	L/240	L/360	L/600	L/240	L/360	L/600
12												
16												
24												

Spacing	30psf			35psf			40psf			50psf		
(inches)	L/240	L/360	L/600									
12												
16												
24												

#### **Additional Specification Information**

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

#### **LEED Specification Information**

Materials & Resources Credit 2: Construction Waste Management - Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. (1 point)

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10%(based on cost) of the total value of the materials in the project.

Credit 4.2 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com.

Studs Unlimited is located in Oklahoma City, Oklahoma. (1 point)

1000S250-68 Page 2