



www.studsunlimited.com

Product Category: 05 41 00 - Structural Framing
Product Name: 800T200-43

Important Properties Notes:

- Calculated properties are based on AISI S100-12 with S2-10 Supplement, North American Specification for Design of Cold-Formed Steel Structural Members.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-section of the studs, away from punchouts.
- For deflection calculations, use the effective
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be specified. (ex. 362S162-43 (50 ksi))

Project Information

Name:
Address:

Contractor Information

Name:
Contact:
Phone:
Fax:

Architect Information

Name:
Contact:
Phone:
Fax:


Distributor/Rep Information

Name:
Contact:
Phone:
Email /Web:

Properties

800T200-43 Properties

Finish: G60
Web Depth 8" in
Flange Width 2" in
Design Thickness 0.0451 in
Thickness 43mils or 18G
Yield stress, F_y 33 ksi
Weight 1.84 lb/ft



800T200-43 Section Properties

Gross Section Properties

Cross sectional area (A) 0.541 in²
Moment of inertia (I_x) 4.888 in⁴
Section Modulus (S_x) 1.198 in³
Radius of gyration (R_x) 3.006 in
Gross moment of inertia (I_y) 0.175 in⁴
Gross Radius of gyration (R_y) 0.569 in

Effective Section Properties

Moment of inertia for deflection (I_{xe}) 4.131 in⁴
Section modulus (S_{xe}) 0.611 in³
Allowable bending moment (M_a) 12.08 in-k
Allowable bending moment from
distortional buckling (M_{ad}) in-K
Allowable strong axis shear away
from punch-out (V_{ag}) 1030 lb
Allowable strong axis shear at
punch out (V_{anet}) - lb

Torsional Properties

St. Venant torsion constant (J x 1000) 0.367 in⁴
Warping constant (C_w) 2.124 in⁶
Distance from shear center to neutral
axis (X₀) -1.886 in
Distance from shear center to
mid-plane (M) 1.56 in
Radii of gyration (R₀) 3.594 in
Torsional flexural constant (Beta) 0.725
Unbraced Length (L_u) 40.3 in



Product Category: 05 41 00 - Structural Framing

Product Name: 800T200-43

Additional Specification Information

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

LEED Specification Information

Materials & Resources Credit 2: Construction Waste Management - Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. **(1 point)**

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10% (based on cost) of the total value of the materials in the project.

Credit 4.2 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com. Studs Unlimited is located in Oklahoma City, Oklahoma. **(1 point)**