

Product Category: 05 41 00 - Structural Framing Product Name: 1400T125-68

Important Properties Notes:

• Calculated properties are based on AISI S100-12 with S2-10 Supplement, North American Specification for Design of Cold-Formed Steel Structural Members.


- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength
- cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-
- section of the studs, away from punchouts.
- For deflection calculations, use the effective
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be

specified. (ex. 362S162-43 (50 ksi))

Properties

1400T125-68 Properties

Finish:	G60
Web Depth	14" in
Flange Width	1 5/8 in
Design Thickness	0.0713 in
Thickness	68mils or 14G
Yield stress, Fy	50 ksi
Weight	3.99 lb/ft



www.studsunlimited.com

Project Information

Name: Address:

Contractor Information Name:

Contact: Phone: Fax:

Architect Information

Name: Contact: Phone: Fax:

Distributor/Rep Information

Contact: Phone: Email /Web:

1400T125-68 Section Properties

Gross Section Properties

Cross sectional area (A)	1.175 in2
Moment of inertia (Ix)	25.208 In4
Section Modulus (Sx)	3.538 in ₃
Radius of gyration (Rx)	4.631 in
Gross moment of inertia (ly)	0.076 in4
Gross Radius of gyration (Ry)	0.254 in

Effective Section Properties

Moment of inertia for deflection (Ixe)	22.871	in4
Section modulus (Sxe)	2.017	inз
Allowable bending moment (Ma)	60.4	In-k
Allowable bending moment from		In-K
distortional buckling (Mad)		
Allowable strong axis shear away	2322	lb
from punch-out (Vag)		
Allowable strong axis shear at	-	lb
punch out (Vanet)		

Torsional Properties

St. Venant torsion constant (J x 1000)	1.992 in4
Warping constant (Cw)	3.189 in6
Distance from shear center to neutral	-1.076 in
axis (Xo)	
Distance from shear center to	0.987 in
mid-plane (M)	
Radii of gyration (Ro)	4.761 in
Torsional flexural constant (Beta)	0.949
Unbraced Length (Lu)	17.1 in

www.studsunlimited.com



Product Category: 05 41 00 - Structural Framing Product Name: 1400T125-68

Additional Specification Information

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

LEED Specification Information

Materials & Resources Credit 2: Construction Waste Management - Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. (1 point)

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10% (based on cost) of the total value of the materials in the project.

Credit 4.2 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com. Studs Unlimited is located in Oklahoma City, Oklahoma. (1 point)