

Product Category: 092216 - Non-Structural Framing

Product Name: 162T200-18

### **Important Properties Notes:**

- Calculated properties are based on AISI S100-12 with S2-10
   Supplement, North American Specification for Design of Cold-Formed
   Steel Structural Members.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on fullsection of the studs, away from punchouts.
- · For deflection calculations, use the effective
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be

specified. (ex. 362S162-43 (50 ksi))

### **Project Information**

Name: Address:

# **Contractor Information** Name:

Contact:
Phone:
Fax:

#### **Architect Information**

Name: Contact: Phone: Fax:


### **Distributor/Rep Information**

Name: Contact: Phone: Email /Web:

# **Properties**

## 162T200-18 Properties

Finish:	G60	
Web Depth	1-5/8"	in
Flange Width	2"	
Design Thickness	0.0188	
Yield stress, Fy	33	
Weight	0.360	lb/ft



# 162T200-18 Section Properties

### **Gross Section Properties**

Cross sectional area (A)	0.106 in2
Moment of inertia (lx)	0.063 In4
Section Modulus (Sx)	0.072 in
Radius of gyration (Rx)	0.77 in4
Gross moment of inertia (ly)	0.046 in
Gross Radius of gyration (Ry)	0.662 in2

### **Effective Section Properties**

Moment of inertia for deflection (lxe)	-	in4
Section modulus (Sxe)	-	in3
Allowable bending moment (Ma)	-	In-lbs
(Vag)	-	lb
Ycg	-	
Fya	33	ksi

### **Torsional Properties**

St. Venant torsion constant (J x 1000)	0.012 In4
Warping constant (Cw)	0.025 in6
Distance from shear center to neutral	-1.905 in
axis (Xo)	
m	1.201
Radii of gyration (Ro)	2.159 in
Torsional flexural constant (Beta)	0.221
Unbraced Length (Lu)	39.2

162T200-18 Page 1





Product Category: 05 41 00 - Structural Framing

Product Name: 162T200-18

### **Additional Specification Information**

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003.

### **LEED Specification Information**

Materials & Resources Credit 2: Construction Waste Management - Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. (1 point)

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10%(based on cost) of the total value of the materials in the project.

Credit 4.2 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com.

Studs Unlimited is located in Oklahoma City, Oklahoma. (1 point)

162T200-18 Page 2