

Product Category: 092216 - Non-Structural Framing Product Name: 362PWT200-19

### **Important Properties Notes:**


• Calculated properties are based on AISI S100-12 with S2-10 Supplement, North American Specification for Design of Cold-Formed Steel Structural Members.

• The centerline bend radius is based on inside corner radii shown in thickness chart.

- Effective properties incorporate the strength
- cold work of forming as applicable per AISI A7.2.
- · Tabulated gross properties are based on full-
- section of the studs, away from punchouts.
- For deflection calculations, use the effective
- Allowable moment includes cold-work of forming.

## **Properties**

<u>362PWT200-19</u>		<u>Properties</u>
Finish:	G40	
Web Depth	3-5/8"	in
Flange Width	2"	in
Design Thickness	0.02	
Yield stress, Fy		ksi
Weight	0.520	lb/ft



### www.studsunlimited.com

### Project Information Name: Address:

# Contractor Information

Contact: Phone: Fax:

Architect Information Name: Contact: Phone: Fax:

**Section Properties** 

Distributor/Rep Information Name: Contact: Phone: Email /Web:

#### **Gross Section Properties** Cross sectional area (A) 0.152 in2 0.354 In4 Moment of inertia (lx) 0.19 in Section Modulus (Sx) 1.523 in4 Radius of gyration (Rx) 0.064 in 0.520 lb/ft Gross moment of inertia (ly) 0.647 in2 Gross Radius of gyration (Ry) **Effective Section Properties** Moment of inertia for deflection (Ixe) in4 Section modulus (Sxe) inз Allowable bending moment (Ma) In-lbs \_ lb (Vag) \_ Ycg Fya 55 ksi **Torsional Properties** St. Venant torsion constant (J x 1000) 0.02 in4 Warping constant (Cw) 0.154 in6

362PWT200-19

Distance from shear center to neutral	-1.279 in
axis (Xo)	
Dist from shear center to mid plain (m)	0.759
Radii of gyration (Ro)	2.091 in
Torsional flexural constant (Beta)	0.626



## Product Category: 092216 - Non-Structural Framing Product Name: 362PWT200-19

### **Additional Specification Information**

Studs Unlimited is an SFIA member. Studs Unlimited acts in accordance with the product and quality standards required by the SFIA program.

Studs Unlimited meets or exceeds ASTM C955, A653, and A1003. Prime Wall is owned by and licensed by MRI Steel Framing

### **LEED Specification Information**

Materials & Resources Credit 2: Construction Waste Management - Studs Unlimited Steel Framing Products are formed from steel and are 100% recyclable. (1 point)

Materials & Resources Credit 4: Recycled Content intends to increase demand for building products that incorporate recycled content materials, therefore reducing impacts resulting from extraction and processing of new virgin materials. As discussed and demonstrated below, North American steel building products contribute positively toward points under Credits 4.1 and 4.2. The following is required by LEED-NC Versions 2.2 and 2009:

Credit 4.1 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 10% (based on cost) of the total value of the materials in the project.
Credit 4.2 (1 point) Use materials with recycled content such that the sum of post-consumer recycled content plus one-half of pre-consumer content constitutes at least 20% of the total value of the materials in the project.

Materials & Resources Credit 5: Regional Materials - Contact Studs Unlimited directly for information at bjpowell@studsunlimited.com. Studs Unlimited is located in Oklahoma City, Oklahoma. (1 point)